

650V 40A Trench and Field Stop IGBT

JJT40N65UK

Key Features:

- $V_{CE} = 650V$
- $I_C = 40A @ V_{CE} = 100$
- $V_{CE(sat)} = 1.9V$


TO-247i

Features:

- Trench and field-stop technology.
- Easy parallel switching capability.

Benefits:

- High efficiency for inverters.
- High ruggedness performance.
- RoHS compliant.



Applications:

- PFC applications
- Welding machines

Package

Type	Marking	Package	Packaging Method
JJT40N65UK	T4065UK	TO-247i	Tube

M

	P		
CES	Collector-emitter voltage	650	V
GES	Gate-emitter voltage	±20	V
C	Continuous collector current ($T_C=25^\circ\text{C}$)	80	A
	Continuous collector current ($T_C=100^\circ\text{C}$)	40	A
CM	Pulsed collector current, I_P limited by t_{vjmax}	160	A
F	Diode continuous forward current ($T_C=100^\circ\text{C}$)	40	A
FM	Diode maximum current, I_P limited by t_{vjmax}	160	A
tot	Power dissipation ($T_C=25^\circ\text{C}$)	174	W
	Power dissipation ($T_C=100^\circ\text{C}$)	87	W
vj	Operating junction temperature range	-40 to +175	
stg	Storage temperature range	-55 to +150	

	P			
		h	th	
th(j-c)	Thermal resistance, junction to case for IGBT	-	0.86	K/ W
th(j-c)	Thermal resistance, junction to case for Diode	-	1.4	K/ W
th(j-a)	Thermal resistance, junction to ambient	-	40	K/ W

**E** **IGB** ($v_j=25$ unless otherwise specified)

Static characteristics

	P					
			M .	.	M .	
$_{CES}$	Collector-emitter breakdown voltage	$_{GE}=0V, I_C=250\mu A$	650	-	-	V
$_{CES}$	Collector-emitter leakage current	$_{CE}=650V, _{GE}=0V$	-	-	50	μA
$_{GES}$	Gate leakage current, forward	$_{GE}=20V, _{CE}=0V$	-	-	100	nA
	Gate leakage current, reverse	$_{GE}=-20V, _{CE}=0V$	-	-	-100	nA
$_{GE(th)}$	Gate-emitter threshold voltage	$_{GE}=_{CE}, _C=1mA$	4.0	5.0	6.0	V
$_{CE(sat)}$	Collector-emitter saturation voltage	$_{GE}=15V, _C=40A$	-	1.9	-	V
		$_{GE}=15V, _C=40A, _{vj}=175$	-	2.6	-	V

Dynamic characteristics

	P					
			M .	.	M .	
$_{ies}$	Input capacitance	$_{CE}=30V$ $_{GE}=0V$ $=1MHz$	-	2480	-	pF
$_{oes}$	Output capacitance		-	95	-	pF
$_{res}$	Reverse transfer capacitance		-	21	-	pF
$_g$	Total gate charge	$_{CC}=520V$ $_{GE}=15V$ $_C=40A$	-	78	-	nC

Switching characteristics

	P					
			M .	. M .	M .	
d(on)	Turn-on delay time	$V_{CC}=400V$ $V_{GE}=0/15V$ $I_C=40A$ $R_G=10\Omega$ Inductive load	-	32	-	ns
r	Rise time		-	55	-	ns
d(off)	Turn-off delay time		-	106	-	ns
f	Fall time		-	51	-	ns
on	Turn-on energy		-	0.9	-	mJ
off	Turn-off energy		-	0.5	-	mJ
ts	Total switching energy		-	1.4	-	mJ
d(on)	Turn-on delay time	$V_{CC}=400V$ $V_{GE}=0/15V$ $I_C=40A$ $R_G=10\Omega$ Inductive load $v_{vj}=175$	-	28	-	ns
r	Rise time		-	52	-	ns
d(off)	Turn-off delay time		-	128	-	ns
f	Fall time		-	75	-	ns
on	Turn-on energy		-	1.4	-	mJ
off	Turn-off energy		-	0.7	-	mJ
ts	Total switching energy		-	2.1	-	mJ






Fig 1. Typical output characteristic ($v_j=25$)




Fig 2. Typical output characteristic ($v_j=175$)




Fig 3. Power dissipation as a function of




Fig 4. Typical switching time as a function of C




Fig 5. Typical $V_{GE(th)}$ as a function of v_j




Fig 6. Typical V_F as a function of v_j




Fig 7. Typical CE_{sat} as a function of v_j




Fig 8. Typical Gate charge




Fig 9. Typical switching times as a function of G




Fig 10. Typical switching energy losses as a function of I_c




Fig 11. Typical switching energy losses as a function of G




Fig 12. Typical V_F as a function of I_F




Fig 13. Typical capacitance as a function of V_{ce}
($f=1\text{MHz}$, $V_{GE}=0\text{V}$)





Fig 14. Transient thermal impedance of IGBT

P

TO-247i



Ref.	Dimensions					
	Millimeters			Inches		
	Min.	Typ.	Max.	Min.	Typ.	Max.
A	15.95	16.00	16.05	0.627	0.629	0.631
B	21.85	21.90	21.92	0.860	0.862	0.864
B1	5.15	5.20	5.25	0.202	0.204	0.206
B2	4.32	4.37	4.42	0.170	0.172	0.174
C	19.01	19.11	19.21	0.748	0.752	0.756
D	2.07	2.10	2.13	0.081	0.082	0.083
E	3.07	3.10	3.13	0.120	0.122	0.123
F	1.15	1.20	1.25	0.045	0.047	0.049
G	5.45REF			0.214REF		
G1	5.85	5.90	5.95	0.230	0.232	0.234
G2	-	0.60	-	-	0.023	-
G3	1.76	1.81	1.86	0.069	0.071	0.073
H	4.95	5.00	5.05	0.194	0.196	0.198
J	1.44	1.49	1.54	0.056	0.058	0.060
K	2.30	2.35	2.40	0.090	0.092	0.094
L	0.59	0.60	0.61	0.023	0.023	0.024
L1	1.85	1.90	1.95	0.072	0.074	0.076



Date	Revision	Changes
2026-06-01	Rev 1.0	Release of the datasheet

D

PLEASE NOTE - Jiangsu JieJie Microelectronics Co., Ltd ("JJM") reserves the right to amend, correct, modify and enhance the product and/or this document at any time without prior notice. If you intend to purchase this product, please obtain the latest information available before placing your order. The sale of JJM products is governed by JJM's prevailing terms and conditions at the time of purchase and purchasers are solely responsible for the selection and use of the products with no liability on JJM's part to supply application assistance or customization. Purchase of JJM products does not grant the purchaser license, express or implied, to JJM's intellectual property. Any warranties provided with JJM products are null and void upon resale unless accompanied by the information set forth herein in its entirety. The JJM name and logo are registered trademarks of Jiangsu JieJie Microelectronics Co., Ltd. This document supersedes all previous versions. ©2026 JJM - All rights reserved